



# STANDARD LED LAMPS (CYLINDRICAL TYPES)

Package	Part No.	Chip		Lens Appearance	Absolute Maximum Ratings				Electro-optical Data(At 20mA)			Viewing Angle 2 $\theta$ 1 $\pm$ 2 (deg)	Drawing No.
		Material/Emitted Color	Peak Wave Length I <sub>P</sub> (nm)		I (nm)	Pd (mw)	If (mA)	Peak (mA)	Vf (V)		Iv (mcd)		
									Typ	Max	Typ		
Cylindrical 0.5" Lead 4.5	BL-C5121	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.2	150	L-040
	BL-C4521	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	9.0		
	BL-C2121	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	9.0		
	BL-C3121	GaP/GaP/Hi-Eff Green	585	Yellow Diffused	35	80	30	150	2.1	2.6	8.0		
1.0" Lead Cylindrical 3.0	BL-C5132	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	3.0	130	L-041
	BL-C4532	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	9.0		
	BL-C2132	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	9.0		
	BL-CX1132	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	12.0		
	BL-C3132	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	8.0		
	BL-C4132	GaAsP/GaP/Orange	635	Orange Diffused	45	100	30	150	2.0	2.6	9.0		
1.0" Lead Cylindrical 3.0	BL-C5435	GaP/GaP/Bright Red	700	Red Trans	90	40	15	50	2.2	2.6	5.0	120	L-042
	BL-C4635	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	15.0		
	BL-C2435	GaP/GaP/Green	568	Green Trans	30	80	30	150	2.2	2.6	15.0		
	BL-CX1435	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	18.0		
	BL-C3435	GaAsP/GaP/Yellow	585	Yellow Trans	35	80	30	150	2.1	2.6	12.0		
	BL-C4435	GaAsP/GaP/Orange	635	Orange Trans	45	100	30	150	2.0	2.6	15.0		
1.0" Lead Cylindrical 5.0	BL-C5436	GaP/GaP/Bright Red	700	Red Trans	90	40	15	50	2.2	2.6	5.0	120	L-043
	BL-C4636	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	14.0		
	BL-C2436	GaP/GaP/Green	568	Green Trans	30	80	30	150	2.2	2.6	14.0		
	BL-CX1436	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	16.0		
	BL-C3436	GaAsP/GaP/Yellow	585	Yellow Trans	35	80	30	150	2.1	2.6	13.0		
	BL-C4436	GaAsP/GaP/Orange	635	Orange Trans	45	100	30	150	2.0	2.6	14.0		



# STANDARD LED LAMPS (CYLINDRICAL TYPES)

L-040 BL-Cxx21 Series	L-041 BL-Cxx32 Series
L-042 BL-Cxx35 Series	L-043 BL-Cxx36 Series

- Notes: 1. All Dimensions are in millimeters (inches).  
 2. Tolerance is  $\pm 0.25\text{mm}$  (.010")



# STANDARD LED LAMPS (TOWER TYPES)

Package	Part No.	Chip		Lens Appearance	Absolute Maximum Ratings				Electro-optical Data (At 20mA)			Viewing Angle 2q 1/2 (deg)	Drawing No.
		Material/Emitted Color	Peak Wave Length $\lambda_p$ (nm)		(nm)	Pd (mw)	If (mA)	Peak (mA)	Vf (V)		Iv (mcd)		
									Typ	Max	Typ		
Panel Dot 1.0" Lead 1.75	BL-S5131	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.2	75	L-044
	BL-S4531	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	6.0		
	BL-S2131	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	6.0		
	BL-S3131	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	4.0		
1.0" Lead Tower $\phi$ 3.0	BL-S5132	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.2	100	L-045
	BL-S4532	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	6.0		
	BL-S2132	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	6.0		
	BL-SX1132	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	9.0		
	BL-S3132	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	5.0		
	BL-S4132	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	6.0		
1.0" Lead Tower $\phi$ 2.75	BL-S5133	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.4	100	L-046
	BL-S4533	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	6.0		
	BL-S2133	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	6.0		
	BL-SX1133	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	9.0		
	BL-S3133	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	5.0		
	BL-S4133	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	6.0		
1.0" Lead Tower $\phi$ 2.0	BL-S5136	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.2	70	L-047
	BL-S4536	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	7.0		
	BL-S2136	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	7.0		
	BL-SX1136	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	10.0		
	BL-S3136	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	6.0		
	BL-S4136	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	7.0		
1.0" Lead Tower $\phi$ 2.8	BL-S5137	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	15	100	L-048
	BL-S4537	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	22		
	BL-S2137	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	22		
	BL-SX1137	GaP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	25		
	BL-S3137	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	21		
	BL-S4137	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	22		
1.0" Lead Tower $\phi$ 3.0	BL-S5137A	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	15	70	L-049
	BL-S4537A	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	22		
	BL-S2137A	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	22		
	BL-SX1137A	GaAsP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	25		
	BL-S3137A	GaAsP/GaP/Orange	585	Yellow Diffused	35	80	30	150	2.1	2.6	21		
	BL-C4137A	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	22		
1.0" Lead Tower $\phi$ 1.8	BL-S51L8	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.0	70	L-050
	BL-S45L8	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	5.0		
	BL-S21L8	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	5.0		
	BL-SX11L8	GaAsP/GaP/Hi-Eff Green	568		30	80	30	150	2.2	2.6	8.0		
	BL-S31L8	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	4.0		
	BL-S41LL8	GaAsP/GaP/Orange	635	Orange Diffused	45	80	30	150	2.0	2.6	5.0		
1.0" Lead Tower $\phi$ 2.0	BL-S5149	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.0	100	L-051
	BL-S4549	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	8.0		
	BL-S2149	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	8.0		
	BL-S31149	GaAsP/GaP/Green	568	Yellow Diffused	30	80	30	150	2.2	2.6	7.0		
	BL-S4149	GaAsP/GaP/Orange	635	Orange Diffused	35	80	30	150	2.1	2.6	8.0		
1.0" Lead Tower $\phi$ 2.0	BL-S5149A	GaP/GaP/Bright Red	700	Red Diffused	90	40	15	50	2.2	2.6	1.0	120	L-052
	BL-S4549A	GaAsP/GaP/Hi-Eff Red	635		45	80	30	150	2.0	2.6	8.0		
	BL-S2149A	GaP/GaP/Green	568	Green Diffused	30	80	30	150	2.2	2.6	8.0		
	BL-S31149A	GaAsP/GaP/Yellow	585	Yellow Diffused	35	80	30	150	2.1	2.6	7.0		

- Remark: 1. Hi-eff Red/High-Efficiency Red.  
2. Trans/Transparent.  
3.  $2\theta$  1/2 The off-axis angle at which the luminous intensity is half the axial luminous intensity.



# STANDARD LED LAMPS (TOWER TYPES)

L-044 BL-Sxx31 Series	L-045 BL-Sxx32 Series
L-046 BL-Sxx33 Series	L-047 BL-Sxx36 Series
L-048 BL-Sxx37 Series	L-049 BL-Sxx37A Series
L-050 BL-SxxL8 Series	L-051 BL-Sxx49 Series

Notes: 1. All Dimensions are in millimeters (inches).  
 2. Tolerance is  $\pm 0.25\text{mm}$  (.010")



# STANDARD LED LAMPS (TOWER TYPES)

L-052	BL-Sxx49A Series	
<p>Technical drawing of the BL-Sxx49A Series LED lamp. The drawing includes a side view, a top view, and a detail view of the base. Dimensions are provided in inches and millimeters. Key features include a cathode, a square base, and a maximum height of 1.5 inches. The drawing is labeled with various dimensions and tolerances.</p> <p>Dimensions (inches in parentheses):</p> <ul style="list-style-type: none"><li>1.6(.062)</li><li>2.0(.078)</li><li>3.1(.122)</li><li>0.5(.02)</li><li>1.5(.06)</li><li>0.5(.02)</li><li>2.7(.11)</li><li>2.65(.104)</li><li>2.75(.11)</li><li>1.5(.059) MAX.</li><li>25.4(1.00) MIN.</li><li>0.5(.02) SQ. TYP.</li><li>CATHODE</li><li>1.0(.039) MIN.</li><li>3.7(.145)</li><li>2.75(.11)</li><li>2.54(.100) NOM.</li></ul>		